



**QC TRI PRO-3.3X Specifications**

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 323 Watts / Low: 274 Watts	
Air Flow	Hi: 3216 CFM / Low: 2890 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	2450 CFM	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 1610 SQ FT	
# of Speeds	2	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	4.29 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 22 1/4"	
Removable Grille Outside Dimension	16" x 24"	
Shipping Weight	55 lbs.	
Box Dimensions	27" x 20" x 38"	
In The Box	<ul style="list-style-type: none"> <li>-QC STL PRO-3.3X Motorhead</li> <li>-Removable Grille</li> <li>-Cut-out Template</li> <li>-Window Locks</li> </ul>	<ul style="list-style-type: none"> <li>-Damper Box</li> <li>-6 Foot Duct</li> <li>-Accessory Bag</li> <li>-Controls</li> </ul>



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)