



QC ES-3100 Specifications

	1	
Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 285 Watts / Low: 80.8 Watts	
Air Flow	Hi: 3081 CFM / Low: 2020 CFM	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 1550 SQ FT	
# of Speeds	2	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls (Not Included)	Recommended 8 Hour Electronic Timer (IT-30070) and	
	HI-LOW-OFF Switch (IT-35000)	
Warranty	10 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	4.11 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 22 1/4"	
Removable Grille Outside Dimension	16" x 24"	
Shipping Weight	56 lbs.	
Box Dimensions	27" x 20" x 38"	
In The Box	-QC ES-3100 Motorhead	-Damper Box
	-Ceiling Grille	-6 Foot Duct
	-Cut-out Template	-Accessory Bag
	-Window Locks	



For more information, visit our website at: QUIETCOOLSYSTEMS.COM