



QC STL PRO-5.5X
QuietCool Stealth Pro Line

QC STL PRO-5.5X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 490 Watts / Med: 268 Watts / Low: 88 Watts	
Air Flow	Hi:5044 CFM / Med:4238 CFM / Low:2870 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	3750 CFM	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 2530 SQ FT	
# of Speeds	3	
Duct Diameter	20"	
Duct Length	9 feet	
Motor Head Diameter	20 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	6.73 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 30 1/4"	
Removable Grille Outside Dimension	16" x 32"	
Shipping Weight	97 lbs.	
Box Dimensions	39" x 24" x 39"	
In The Box	<ul style="list-style-type: none"> -QC STL PRO-5.5X Motorhead -Removable Grille -Cut-out Template -Window Locks 	<ul style="list-style-type: none"> -Damper Box -9 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM