



QC TRI PRO-2.5X
QuietCool Trident Pro Line

QC TRI PRO-2.5X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 244 Watts / Low: 198 Watts	
Air Flow	Hi: 2490 CFM / Low: 1934 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	1800 CFM	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers up to 1250 SQ FT	
# of Speeds	2	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and HI-LOW-OFF Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	3.32 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 18 1/4"	
Removable Grille Outside Dimension	16" x 20"	
Shipping Weight	49 lbs.	
Box Dimensions	24" x 20" x 38"	
In The Box	-QC TRI PRO-2.5X Motorhead -Removable Grille -Cut-out Template -Window Lock	-Damper Box -6 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM