

**QC STL PRO-6.0X RF**  
**QuietCool Stealth Pro Line**

**QC STL PRO-6.0X RF Specifications**

Airflow	Hi: 5,587 CFM / Med: 4,262 CFM / Low: 3,428 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 4,030 CFM / Med: 3,070 CFM / Low: 2,440 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,862 SQFT to 2,794 SQFT
Energy Use	Hi: 462 Watts / Med: 210 Watts / Low: 113 Watts
Amps	Hi: 5.91 / Med: 2.90 / Low: 1.65
Motor Voltage	120 VAC, 60 Hz
# of Speeds	3
dBA	Hi: 49.3 / Med: 42.5 / Low: 38.5
Minimum Attic Clearance	42"
Duct Diameter	22"
Duct Length	9 feet
Motor Head Diameter	22 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	7.45 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	96 lbs.
Box Dimensions	41" x 26" x 39"
In The Box	-QC STL PRO-6.0X Motorhead -Damper Box -Ceiling Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks -Wireless RF Control Kit



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)