

**QC TRI PRO-5.5X RF**  
**QuietCool Trident Pro Line**

**QC TRI PRO-5.5X RF Specifications**

Airflow	Hi: 5,068 CFM / Low: 4,438 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 3,940 CFM / Low: 3,220 CFM
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1,689 SQFT to 2,534 SQFT
Energy Use	Hi: 632 Watts / Low: 522 Watts
Amps	Hi: 5.56 / Low: 4.53
Motor Voltage	120 VAC, 60 Hz
# of Speeds	2
dBA	Hi: 51.2 / Low: 45.7
Minimum Attic Clearance	38"
Duct Diameter	20"
Duct Length	9 feet
Motor Head Diameter	20 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included IT-36003 QuietCool Wireless RF Control Kit with Glass Wireless RF Switch
Warranty	Limited Lifetime
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	6.76 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 30 1/4"
Removable Grille Outside Dimension	16" x 32"
Shipping Weight	75 lbs.
Box Dimensions	39" x 24" x 39"
In The Box	-QC TRI PRO-5.5X Motorhead    -Damper Box -Ceiling Grille                    -9 Foot Duct -Cut-out Template                -Accessory Bag -Window Locks                    -Wireless RF Control Kit



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)